



LUBE

- Brake cables lubricated
- Derailleur cables lubricated
- Pedal threads lubricated and pedals tight
- Stem greased
- Seat post greased

SEAT

- Seat post inserted not higher than max. Safe height or min. insert mark. Seat post tight.
- Seat level and tight

HANDLE BARS

- Headset adjusted and top nut locked down
- Handlebar binder tight
- Stem inserted not higher than max. Safe height or min. insert mark. Stem bolt tight

WHEEL

- Dropouts and fork tips parallel
- Hubs adjusted
- Wheels true
- Wheels centered with quick releases adjusted and tight. Front lever parallel to fork and rear lever between left seat and chain stays, or axle nuts tight.

REFLECTORS

- Wheel reflectors installed
- Pedal reflectors installed
- Front and rear reflectors installed

BRAKES

- Brake lever bolts tight
- Cantilever or caliper brake mounting bolts tight
- Brake pads adjusted and tight
- Brake adjusting barrel screwed all the way in
- Brake cables fully pre-stressed
- Brake cables readjusted

CHAIN WHEEL

- Bottom bracket adjusted
- Chain wheel bolts tight
- Crank arm bolts tight

DERAILLEUR

- Derailleur hanger aligned
- Derailleur hanger bolt tight
- Shift levers tight
- Cable stops and guides tight
- Cable casing seated
- Rear derailleur adjusted
- Front Derailleur adjusted
- Cable ends capped or soldered

AIR PRESSURE

- Air in tires to recommended pressure
- Tires inspected for proper mounting to rim
- Valve caps on

ACCESSORIES

- Toe clips and straps installed and tightened
- Kickstand straight and tight
- Other accessories installed and tight

FINISH UP

- Easy gear selected
- Bike clean and free of excess grease and oil

WITH BIKE ON THE FLOOR

- Stem to steer tube force-checked for looseness
- Handlebars to stem force-checked for looseness
- Seat post and seat force-checked for looseness
- Freewheel cranked tight by pedal force

TEST RIDE BIKE

X _____

Renter's Signature

Date